

(19)



P01PLT003EP

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 962 363 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

08.12.1999 Bulletin 1999/49

(51) Int Cl.⁶: B60R 21/16

(21) Application number: 99304115.1

(22) Date of filing: 27.05.1999

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 01.06.1998 JP 15139798

23.04.1999 JP 11681799

(71) Applicant: TAKATA CORPORATION

Minato-ku, Tokyo (JP)

(72) Inventors:

- Mishina, Jyoji, c/o Takata Corporation
Tokyo (JP)
- Masuda, Yasushi, c/o Takata Corporation
Tokyo (JP)
- Nakanishi, Ryosuke, c/o Takata Corporation
Tokyo (JP)

(74) Representative: Jenkins, Peter David et al

PAGE WHITE & FARRER

54 Doughty Street


London WC1N 2LS (GB)

(54) Airbag

(57) An airbag is provided which securely prevents gas leakage through seams between panels and has excellent productivity. The airbag 10 has panels 1, 2. Peripheral portions of the panels 1, 2 are bonded with silicone adhesive 5 and also sewn together by sewing

yarns 6A, 6B. Seams of the sewing yarns 6A, 6B may be coated by silicone sealant. The sewing yarn 6A composing an inner seam is thinner than the sewing yarn 6B composing an outer seam so that the sewing yarn 6A is broken during the inflation of the airbag 10, thereby absorbing energy.

Fig. 1b



EP 0 962 363 A1

Description

[0001] The present invention relates to an airbag for an airbag device installed in a conveyance including a vehicle and an aircraft and, more particularly, to an airbag where gas is prevented from leaking from seams between panels.

[0002] An vehicle airbag for an automobile, such as a driver's airbag, a front passenger's airbag, a rear passenger's airbag, and a side airbag, or an airbag for an aircraft, has a plurality of panels which are sewn together in a bag-like configuration. The airbag is inflated by gas supplied from an inflator.

[0003] As for an airbag, which is difficult to retain its internal pressure, for example a side airbag (of a curtain type) for protecting a head of an occupant and a side airbag for coping with roll over, it is desired to extremely prevent gas leakage through seams.

[0004] In order to prevent gas leakage through seams between panels, as shown in Figs. 4a, 4b, silicone tapes 4 are attached along peripheries of panels 1', 2' to cover a seam 3' of the panels 1', 2'.

[0005] The conventional airbag in Figs. 4a, 4b, the silicone tapes 4 must be attached to the both surfaces of the airbag, thereby increasing the man-hour and impairing the productivity. When high pressure gas is introduced into the airbag, there is a possibility of gas leakage through a clearance between the panels 1', 2' as shown in an arrow G in Fig. 4b. Therefore, the amount of gas to be supplied by the inflator must be increased in consideration of the amount of gas leakage, so the capacity of the inflator should be large.

[0006] The aim of the present invention is to provide an airbag where gas is prevented from leaking at seams between panels and which has excellent productivity.

[0007] An airbag of the present invention has a first panel and a second panel, peripheral portions of which are connected to each other by sewing by yarn and bonding by silicone adhesive.

[0008] The airbag of the present invention has little or no gas leakage, since the first panel and the second panel are not only sewn together but also bonded by the silicone adhesive along their peripheries. When the panels are sewn together after bonding the panels with the silicone adhesive, the panels are prevented from slipping to each other during the sewing operation, thus improving the sewing workability.

[0009] The seams may include a first seam positioned outside and a second seam positioned inside, and sewing yarn for the second seam may be thinner than sewing yarn for the first seam. The sewing yarn for the second seam positioned inside is broken during the inflation of the airbag so as to partially absorb energy of gas pressure. This energy absorption reduces the impact applied to the sewing yarn for the first seam positioned outside during the inflation of the airbag.

[0010] The seam of the panels may be covered by silicone sealant, thereby preventing the gas leakage at the

stitches.

[0011] Embodiments of the present invention will now be described by way of example only, with reference to the accompanying drawings, in which:-

Fig. 1a is a perspective view showing an embodiment of an airbag according to the present invention, Fig. 1b is an enlarged sectional view taken along a line IB-IB of Fig. 1a, Fig. 1c is an enlarged sectional view of a part of the peripheries of the airbag when inflated;

Fig. 2 is an enlarged sectional view of the part of the peripheries of the airbag when fully inflated;

Fig. 3 is a sectional view of a part of the peripheries of an airbag according to another embodiment;

Fig. 4a is a perspective view showing a conventional airbag. Fig. 4b is an enlarged view of a section taken along a line IVB-IVB of Fig. 4a;

Fig. 5 is a side view of an airbag according to another embodiment;

Fig. 6 is a perspective view of the airbag shown in Fig. 5 when inflated; and

Fig. 7 is a sectional view taken along a line VIIA-VIIA of Fig. 6, Fig. 7b is an enlarged view of a VIIB part of Fig. 7a.

[0012] Hereinafter, embodiments of the present invention will be described with reference to the attached drawings.

[0013] Fig. 1a is a perspective view showing an embodiment of an airbag according to the present invention, Fig. 1b is an enlarged sectional view taken along a line IB-IB of Fig. 1a, Fig. 1c is a sectional view of the same part shown in Fig. 1b when the airbag is inflated and deployed.

[0014] Though an airbag 10 shown in Figs. 1a-1c is a side airbag for an automobile, it should be understood that the present invention is not limited thereto and may be applied to automobile airbags for a driver's seat, a front passenger's seat, and a rear passenger's seat and also to an airbag for an aircraft.

[0015] The airbag 10 has a first panel 1 and a second panel 2 which are sewn together along peripheries thereof. The peripheries of the first and second panels 1, 2 are bonded by silicone adhesive 5 and sewn together by sewing yarns 6A, 6B. During the inflation of the airbag 10, as shown in Fig. 1c and Fig. 2, the silicone adhesive 5 stretches following the panels 1, 2 which move apart from each other. The adhesive 5 stretches with being adhered to the panels 1, 2, thereby preventing the gas leakage through a clearance between the panels 1, 2.

[0016] The silicone adhesive 5 bonding the panels 1, 2 to each other has elongation of, preferably, 200% or more. As the silicone adhesive, a RTV (room temperature vulcanizing) silicone rubber is particularly preferable.

[0017] The silicone adhesive 5 is applied along the

peripheries of the panels 1, 2 over a width W from 5 mm to 15 mm (as shown in Fig. 1b) with an amount from 0.01g/cm² to 0.05g/cm².

[0018] The panels 1, 2 are made of woven fabric of synthetic resin. The inner surfaces of the panels 1, 2

may be coated with a silicone resin or rubber for filling.

[0019] In this embodiment, the panels 1, 2 are sewn together along two stitching lines by two sewing yarns 6A, 6B. The inner one of the stitching lines is made with the sewing yarn 6A which is relatively thin to make a second seam and the outer one is made with the sewing yarn 6B which is relatively thick to make a first seam.

According to the airbag which is sewn along the two stitching lines of the peripheries, as shown in Fig. 2, the relatively thin sewing yarn 6A composing the inner stitching line is broken by the pressure of gas supplied from an inflator, thereby partially absorbing the energy of the gas pressure which is exerted on a connection of the panels 1, 2 in the stripping direction. Therefore, the impact exerted in such a direction as to break the first seam composed of the sewing yarn 6B can be reduced, thereby further securely preventing the gas leakage at the connection of the panels 1, 2.

[0020] The relatively thin sewing yarn 6A composing the inner stitching line preferably has fineness about 210-420d (deniers) and the relatively thick sewing yarn 6B composing the outer stitching line preferably has finenesses about 840-1260d. The first seam by the sewing yarn 6B is preferably located apart from the peripheral edges of the panels 1, 2 by a distance about 10-18 mm and the distance (d in Fig. 1b) between the yarn 6B and the yarn 6A is preferably about 2-5 mm.

[0021] The airbag 10 can be made by superposing the panels 1, 2 having a portion to be sewn to which the silicone adhesive 5 is applied and, after that, sewing up them with the sewing yarns 6A, 6B. Since the panels 1, 2 are bonded to each other by the silicone adhesive 5, the panels 1, 2 are prevented from slipping to each other during the serving, thereby improving the sewing workability.

[0022] Though the two sewing yarns are used to stitch the double seams in the airbag shown in Figs. 1a, 1b, 1c, the sewing may be made by using only one sewing yarn. In this case, a sewing yarn having fineness about 840-1260d is preferably used and a portion along and apart from the peripheral edges of the panels by a distance 10-20 mm is preferably stitched.

[0023] As shown in Fig. 3, silicone sealant 7 may be applied to the peripheral edges of the panels 1, 2 to cover the stitching lines of the sewing yarns 6A, 6B. Applying the sealant 7 prevents the gas leakage from the stitching.

[0024] Figs. 5 through 7b show an airbag for protecting the head of an occupant which is disposed along a roof-side member above an automobile door. This airbag 20 has two panels 21, 22 which are connected to each other by silicone adhesive 26 and sewing yarns 23, 24. The airbag 20 comprises a gas introducing por-

tion 25 to be disposed along an Apillar or a C pillar of the automobile. Gas from a gas generator is introduced into the airbag 20 through an opening 25a at a tip of the gas introducing portion 25. The sewing yarn 23 is stitched to connect the peripheral portions of the panels 21, 22 and the sewing yarn 24 is stitched to connect the middle portions of the panels 21, 22. The airbag 20 expands from the roof side to an upper portion of the door so as to receive the head of the occupant. The airbag 20 is sewn together at the middle portions of the panels 21, 22 in order to restrain the thickness (T in Fig. 7a) of the inflated airbag 20 to a predetermined value.

[0025] The form of sewing the panels 21, 22 along the peripheral portions of the panels 21, 22 is the same as that shown in Fig. 1b, that is, the peripheral portions of the panels 21, 22 are bonded with the silicone adhesive and sewn up along two stitching lines by sewing yarns, but the illustration is omitted. One of the sewing yarns composing the inner stitching line is thinner than the other one of the sewing yarns composing the outer stitching line.

[0026] At the middle portions of the panels 21, 22, as shown in Fig. 7b, the panels 21, 22 are bonded with the silicone adhesive 26 and sewn up by the sewing yarn 24 to each other. The sewing yarn 24 comprises a thin yarn 24A and a thick yarn 24B. The yarn 24A is positioned close to an inner chamber 28 of the airbag 20 as compared to the yarn 24B. Therefore, during the inflation of the airbag 20, the thin yarn 24A is broken in the same manner as the case of Fig. 2, thereby partially absorbing the energy applied to the connection of the panels 21, 22 in the stripping direction. As a result of this, the impact in the stripping direction applied to the seam made by the sewing yarn 24B is reduced.

[0027] Though the two sewing yarns 24A, 24B having different thickness are used in the embodiment of Figs. 5-7, only one stitching line may be provided.

[0028] As mentioned above, the present invention provides an airbag which can securely prevent the gas leakage from the connection between the panels and has excellent productivity.

Claims

1. An airbag comprising a first panel and a second panel, peripheral portions of which are connected to each other by connecting means,

wherein said connecting means includes sewing by yarn and bonding by silicone adhesive.

2. The airbag as claimed in claim 1, wherein said sewing by yarn comprises a first seam positioned outside and a second seam positioned inside, and wherein the sewing yarn for the second seam is thinner than the sewing yarn for the first seam.

3. The airbag as claimed in claim 2, wherein the sewing
yam for the second seam is broken during the
inflation of the airbag so as to partially absorb en-
ergy of gas pressure. 5
4. The airbag as claimed in claim 1 or 2, wherein the
seam on the peripheral portions of the panels is cov-
ered by sealant. 10
5. The airbag as claimed in claim 1 or 2, wherein the
seam of silicone adhesive to be applied is from
0.01g/cm² to 0.05g/cm². 15
6. The airbag as claimed in any one of claims 1
through 5, wherein the silicone adhesive is RTV
(room temperature vulcanizing) silicone rubber. 20
7. The airbag as claimed in any one of claims 1
through 6, wherein the panels are made of synthetic
resin woven fabrics. 25
8. The airbag as claimed in claim 7, wherein the inner
surfaces of the panels are coated with silicone resin
or rubber. 30
9. The airbag as claimed in any one of claims 1
through 8, wherein said adhesive stretches with be-
ing adhered to the respective panels. 35

40

45

50

55

60

65

70

Fig. 1a




Fig. 1b




Fig. 1c




Fig. 2




Fig. 3




Fig. 4a




Fig. 4b




Fig. 5




Fig. 6




Fig. 7a





Fig. 7b



EUROPEAN SEARCH REPORT

Application Number
EP 99 30 4115

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	PATENT ABSTRACTS OF JAPAN vol. 014, no. 556 (M-1057), 11 December 1990 (1990-12-11) & JP 02 237837 A (TAKATA KK), 20 September 1990 (1990-09-20) * abstract: figures *	1,7-9	B60R21/16
Y	---	2,3,6	
Y	US 5 511 821 A (SCOTT A. MEYER) 30 April 1996 (1996-04-30) * abstract: claims 8.9 *	2,3	
A	WO 98 12075 A (MINNESOTA MINING AND MANUFACTURING CO.) 26 March 1998 (1998-03-26) * page 11, line 19 - page 12, line 22; claims 1.6,8,15 *	1,7-9	
Y	---	6	
A	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 809, 31 July 1998 (1998-07-31) & JP 10 086776 A (TOAGOSEI CO LTD), 7 April 1998 (1998-04-07) * abstract *	1,7-9	TECHNICAL FIELDS SEARCHED (Int.Cl.6) B60R
A	WO 95 00366 A (SANDIA CORP.) 5 January 1995 (1995-01-05) * page 10, line 3 - page 13, line 8; figures 4,5,15 *	1,7	
A	GB 1 340 549 A (NISSAN MOTOR CO., LTD.) 12 December 1973 (1973-12-12) * page 2, line 60 - line 73 * * page 2, line 125 - page 3, line 18; figure 8 *	1	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 4 October 1999	Examiner Dubois, E
CATEGORY OF CITED DOCUMENTS		- theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure F : intermediate document			



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 30 4115

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	DATABASE WPI Week 9403 Derwent Publications Ltd., London, GB; AN 1994-061839 XP002117332 & JP 06 016099 A (TOSHIBA SILICONE KK), 25 January 1994 (1994-01-25) * abstract; figure *	1	
A	US 3 879 056 A (KAWASHIMA ET AL.) 22 April 1975 (1975-04-22) * column 6, line 7 - line 15; figures 1,3A-3C *	4	
A	GB 2 301 320 A (ASAHI KASEI KOGYO K.K.) 4 December 1996 (1996-12-04) * page 22, line 23 - page 23, line 12 * * page 26, line 17 - page 27, line 21; figure 28 *	5	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
Place of search:		Date of completion of the search	Examiner
THE HAGUE		4 October 1999	Dubois, B
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technical background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

[P.O. FORM 1503 03 02 (P.O. 001)]

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 99 30 4115

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on:
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-10-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 02237837 A	20-09-1990	JP 1798743 C	12-11-1993
		JP 5009305 B	04-02-1993
US 5511821 A	30-04-1996	EP 0718162 A	26-06-1996
		JP 8310325 A	26-11-1996
WO 9812075 A	26-03-1998	AU 4353997 A	14-04-1998
		WO 9914082 A	25-03-1999
JP 10086776 A	07-04-1998	NONE	
WO 9500366 A	05-01-1995	US 5482317 A	09-01-1996
		AT 174273 T	15-12-1998
		AU 685826 B	29-01-1998
		AU 7313994 A	17-01-1995
		CA 2143184 A	05-01-1995
		CN 1112362 A	22-11-1995
		CZ 9500511 A	17-04-1996
		DE 69415134 D	21-01-1999
		DE 69415134 T	29-04-1999
		EP 0656842 A	14-06-1995
		ES 2126132 T	16-03-1999
		HU 70632 A	30-10-1995
		JP 8501517 T	20-02-1996
		PL 307727 A	12-06-1995
		US 5533755 A	09-07-1996
		US 5607182 A	04-03-1997
		ZA 9404600 A	31-01-1995
GB 1340549 A	12-12-1973	AU 3282871 A	01-03-1973
		CA 979940 A	16-12-1975
		DE 2160959 A	22-06-1972
JP 6016099 A	25-01-1994	NONE	
US 3879056 A	22-04-1975	JP 856806 C	28-04-1977
		JP 48087533 A	17-11-1973
		JP 51031581 B	07-09-1976
		JP 856808 C	28-04-1977
		JP 48088629 A	20-11-1973
		JP 51031659 B	08-09-1976
GB 2301320 A	04-12-1996	US 5865464 A	02-02-1999
		CA 2181917 A	03-08-1995
		WO 9520507 A	03-08-1995

EPO FORM P0159

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82